

DAFTAR PUSTAKA

- [1] P. K. Panigrahi and S. K. Bisoy, “Localization strategies for autonomous mobile robots: A review,” *Journal of King Saud University - Computer and Information Sciences*, vol. 34, no. 8, pp. 6019–6039, 2022, doi: 10.1016/j.jksuci.2021.02.015.
- [2] J. Li and S.-H. Hwang, “Improved GNSS positioning schemes in urban canyon environments,” *IEEE Access*, vol. 13, pp. 112354–112367, 2025, doi: 10.1109/ACCESS.2025.3583347.
- [3] J. Borenstein and L. Feng, “Measurement and correction of systematic odometry errors in mobile robots,” *IEEE Transactions on Robotics and Automation*, vol. 12, no. 6, pp. 869–880, 1996, doi: 10.1109/70.544770.
- [4] T. S. Teoh, P. P. Em, and N. A. B. A. Aziz, “Vehicle localization based on IMU, OBD2, and GNSS sensor fusion using Extended Kalman Filter,” *International Journal of Technology*, vol. 14, no. 6, pp. 1237–1246, 2023, doi: 10.14716/ijtech.v14i6.6649.
- [5] A. M. R. M. Saputra, M. Munadi, and J. D. Setiawan, “Simulasi sistem lokalisasi berbasis Extended Kalman Filter pada robot Clearpath Husky,” *Jurnal Teknik Mesin*, vol. 13, no. 1, pp. 57–62, Jan. 2025. [Online]. Available: <https://ejournal3.undip.ac.id/index.php/jtm/article/view/49665>. [Accessed: Sep. 5, 2026].
- [6] A. Kaczmarek, W. Rohm, L. Klingbeil, and J. Tchórzewski, “Experimental 2D extended Kalman filter sensor fusion for low-cost GNSS/IMU/odometers precise positioning system,” *Measurement*, vol. 193, Art. no. 110963, 2022, doi: 10.1016/j.measurement.2022.110963.
- [7] N. B. Muliawan and I. A. Sulistijono, “Sistem lokalisasi mobile-robot pertanian otonom berbasis Ultra-Wideband (UWB) dan sensor inersia,” *Indonesian Journal of Computer Science*, vol. 12, no. 1, pp. 284–301, 2023, doi: 10.33022/ijcs.v12i1.3135.
- [8] N. Muzakki, I. G. P. A. Buditjahjanto, B. Suprianto, and S. A. Alamsyah, “Sistem navigasi berbasis modul kompas & GPS pada prototipe autonomous car dengan pengendali steering metode PI,” *Jurnal Teknik Elektro*, vol. 14, no. 3, pp. 311–318, 2025, doi: 10.26740/jte.v14n3.p311-318.

- [9] M. A. Yaqin, A. Khumaidi, R. Y. Adhitya, N. Rinanto, E. N. Sholikhah, and R. S. F. J. Putra, "Implementasi path planning A* untuk menghindari robot lawan menggunakan Robot Operating System pada KRSBI-Beroda," *Jurnal Elektronika Otomasi Industri*, vol. 12, no. 1, pp. 98–110, May 2025, doi: 10.33795/elkolind.v12i1/7268.
- [10] S. Macenski, M. Booker, J. Wallace, and T. Fischer, "Cost-Aware Kinematically Feasible Planning for Mobile and Surface Robotics," *IEEE Robotics and Automation Practice*, vol. 1, pp. 81–85, 2026, doi: 10.1109/RAP.2026.3684018.
- [11] E. Alverhed, S. Hellgren, H. Isaksson, L. Olsson, H. Palmqvist, and J. Flodén, "Autonomous last-mile delivery robots: A literature review," *European Transport Research Review*, vol. 16, 2024, doi: 10.1186/s12544-023-00629-7.
- [12] T. Qin, S. Cao, J. Pan, and S. Shen, "A general optimization-based framework for global pose estimation with multiple sensors," *arXiv preprint arXiv:1901.03642*, 2019. [Online]. Available: <https://arxiv.org/abs/1901.03642>.
- [13] S. Kato et al., "Autoware on board: Enabling autonomous vehicles with embedded systems," in *Proc. 9th ACM/IEEE International Conference on Cyber-Physical Systems (ICCPS)*, 2018, pp. 287–296, doi: 10.1109/ICCPS.2018.00035.
- [14] u-blox AG, "NEO-M9N module—u-blox M9 standard precision GNSS module," u-blox. [Online]. Available: <https://www.u-blox.com/en/product/neo-m9n-module>. [Accessed: Aug. 25, 2026].
- [15] V. Souza, J. Gaspar, J. F. P. Fernandes, and A. Bernardino, "Localization for car-like vehicles using loosely coupled dual-GNSS integration," *Discover Vehicles*, vol. 2, Art. no. 2, 2026, doi: 10.1007/s44465-026-00004-5.
- [16] L. Mossaberi, I. C. Metz, and S. F. Armanini, "Evaluating UAM–Wildlife Collision Prevention Efficacy with Fast-Time Simulations," *Aerospace*, vol. 13, no. 1, Art. no. 18, 2026, doi: 10.3390/aerospace13010018.
- [17] H. Martin, P. Groves, and M. Newman, "The limits of in-run calibration of MEMS inertial sensors and sensor arrays," *NAVIGATION, Journal of the Institute of Navigation*, vol. 63, no. 2, pp. 127–143, 2016, doi: 10.1002/navi.135.
- [18] T. Zhao, C. Wang, and C. Shen, "Seamless MEMS-INS/geomagnetic navigation system based on deep-learning strong tracking square-root cubature Kalman filter," *Micromachines*, vol. 14, no. 10, Art. no. 1935, 2023, doi: 10.3390/mi14101935.

- [19] C. Liu, S. D. Prior, W. T. L. Teacy, and M. Warner, “Computationally efficient visual–inertial sensor fusion for Global Positioning System–denied navigation on a small quadrotor,” *Advances in Mechanical Engineering*, vol. 8, no. 3, 2016, doi: 10.1177/1687814016640996.
- [20] D. P. Koch, D. O. Wheeler, R. W. Beard, T. W. McLain, and K. M. Brink, “Relative multiplicative extended Kalman filter for observable GPS-denied navigation,” *The International Journal of Robotics Research*, vol. 39, no. 9, pp. 1085–1121, 2020, doi: 10.1177/0278364920903094.
- [21] M. Peiris, H. Lang, and M. El-Gindy, “Kalman filter-based sensor fusion for Ackermann steering mobile robots,” *Journal of Physics: Conference Series*, vol. 2811, no. 1, Art. no. 012004, 2024, doi: 10.1088/1742-6596/2811/1/012004.
- [22] E. Mõtshärg, V. Vunder, R. Raudmäe, M. Muro, I. Drikkitt, L. Tšigrinski, R. Köidam, A. Aabloo, and K. Kruusamäe, “Robotont 3—an accessible 3D-printable ROS-supported open-source mobile robot for education and research,” *Frontiers in Robotics and AI*, vol. 11, 2024, doi: 10.3389/frobt.2024.1406645.
- [23] STMicroelectronics, “STM32F411xC STM32F411xE—Arm Cortex-M4 32-bit MCU+FPU, 125 DMIPS, 512KB Flash, 128KB RAM, USB OTG FS, 11 TIMs, 1 ADC, 13 communication interfaces,” Datasheet DS10314, STMicroelectronics. [Online]. Available: <https://www.st.com/resource/en/datasheet/stm32f411ce.pdf>. [Accessed: Sep. 7, 2026].
- [24] B. Fariña, J. Toledo, J. I. Estevez, and L. Acosta, “Improving robot localization using Doppler-based variable sensor covariance calculation,” *Sensors*, vol. 20, no. 8, Art. no. 2287, 2020, doi: 10.3390/s20082287.
- [25] R. Pizá, R. Carbonell, V. Casanova, Á. Cuenca, and J. J. Salt Llobregat, “Nonuniform dual-rate extended Kalman-filter-based sensor fusion for path-following control of a holonomic mobile robot with four Mecanum wheels,” *Applied Sciences*, vol. 12, no. 7, Art. no. 3560, 2022, doi: 10.3390/app12073560.
- [26] Y. Yin, J. Zhang, M. Guo, X. Ning, Y. Wang, and J. Lu, “Sensor fusion of GNSS and IMU data for robust localization via smoothed error state Kalman filter,” *Sensors*, vol. 23, no. 7, Art. no. 3676, 2023, doi: 10.3390/s23073676.

- [27] S. Macenski, T. Moore, D. V. Lu, A. Merzlyakov, and M. Ferguson, “From the desks of ROS maintainers: A survey of modern & capable mobile robotics algorithms in the Robot Operating System 2,” *Robotics and Autonomous Systems*, vol. 168, Art. no. 104493, 2023, doi: 10.1016/j.robot.2023.104493.
- [28] S. Liu, S. Li, L. Pang, J. Hu, H. Chen, and X. Zhang, “Autonomous exploration and map construction of a mobile robot based on the TGHM algorithm,” *Sensors*, vol. 20, no. 2, Art. no. 490, 2020, doi: 10.3390/s20020490.
- [29] D. Mlinarček, R. Jánoš, M. Málík, J. Svetlík, J. Semjon, and Š. Ondočko, “Costmap tuning for autonomous navigation: A simulation and real-world study on the Hiwonder JetAcker,” *Applied Sciences*, vol. 16, no. 4, Art. no. 1923, 2026, doi: 10.3390/app16041923.
- [30] D. V. Lu, D. Hershberger, and W. D. Smart, “Layered costmaps for context-sensitive navigation,” in *2014 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, Chicago, IL, USA, 2014, pp. 709–715, doi: 10.1109/IROS.2014.6942636.
- [31] Z. Chi, Z. Yu, Q. Wei, Q. He, G. Li, and S. Ding, “High-efficiency navigation of nonholonomic mobile robots based on improved Hybrid A* algorithm,” *Applied Sciences*, vol. 13, no. 10, Art. no. 6141, 2023, doi: 10.3390/app13106141.
- [32] H. Kaartinen et al., “Accuracy of kinematic positioning using global satellite navigation systems under forest canopies,” *Forests*, vol. 6, no. 9, pp. 3218–3236, 2015, doi: 10.3390/f6093218.
- [33] C. Rondoni, F. Scotto di Luzio, C. Tamantini, N. L. Tagliamonte, M. Chiurazzi, G. Ciuti, and L. Zollo, “Navigation benchmarking for autonomous mobile robots in hospital environment,” *Scientific Reports*, vol. 14, Art. no. 18334, 2024, doi: 10.1038/s41598-024-69040-z.