

## DAFTAR PUSTAKA

- Ade Arta, M. Z. (2024). *Analisis co-firing bahan bakar jumptan padat (BBJP) dan batubara terhadap performa pada pulverized coal boiler*.
- Ali, A. M. S., Syaiful, A. Z., & Gazali, A. (2022). Pengaruh senyawa alumina ( $\text{Al}_2\text{O}_3$ ) dan silika ( $\text{SiO}_2$ ) dalam kualitas batubara. *SAINTIS*, 3(1), April 2022.
- Arif, W. Suriyan. (2024). *PT. POMI Coal Fired Power Plant Heat Rate Analysis Manual Training*.
- ASME. (2013). *Fired Steam Generators – Performance Test Codes (PTC) 4-2013*.
- Bhatt, M. S. (2006). *Effect of ash in coal on the performance of coal fired thermal power plants: Part I: Primary energy effects*.
- Cahyono, A. A. (2024). Kementerian Energi dan Sumber Daya Mineral Republik Indonesia. *Siaran Pers Nomor: 28.Pers/04/SJI/2024*.
- Dai, J., et al. (2015). Inhibition of lignite ash *slagging* and *fouling* upon the use of a silica-based additive in an industrial pulverised coal-fired boiler. Part 1. *Fuel*, 139, 720–732. <https://doi.org/10.1016/j.fuel.2014.06.054>
- Direktorat Jenderal Ketenagalistrikan. (2023). *Statistik Ketenagalistrikan Tahun 2022*. Jakarta: Sekretariat Jenderal Ketenagalistrikan.
- Direktorat Jenderal Mineral dan Batubara. (2021). *Roadmap Pemanfaatan dan Pengembangan Batubara 2021–2045*. Kementerian ESDM.
- EtaPRO. (2021). *Performance & Condition Monitoring Administrator Training Workbook*. GP Strategies, New York, USA.
- Feng, Z., Xin, C., Zhou, T., Zhang, J., & Fu, T. (2022). Airside thermal-hydraulic and *fouling* performances of economizers with integrally-molded spiral finned tubes for residual heat recovery.
- Frandsen, F. J. (1997). *Empirical prediction of ash deposition propensities*. Department of Chemical Engineering, Technical University of Denmark.
- Fuel & Ash Report PLTU Superkritikal XYZ. (2024). PT POMI Paiton.
- Ghasidin, H., et al. (2023). Comprehensive evaluation of *slagging* and *fouling* indicators for solid fuel combustion. *Thermal Science and Engineering Progress*.
- Hariana, H., Putra, H. F., & Kuswa, F. M. (2020). Pemilihan batubara Kalimantan untuk PLTU dengan PC Boiler menggunakan tinjauan potensi *slagging* dan *fouling*. *Prosiding Seminar Nasional NCIET*, 1, 48–58.
- Hendri, R., Nurhasanah, & Lubis, A. F. (2021). Characteristic of medium–low rank coal blending on performance and efficiency steam power plant. *IOP Conference Series: Materials Science and Engineering*, 1173.
- International Energy Agency (IEA). (2024). *Electricity 2024: Analysis and forecast to 2026*.

- Kementerian ESDM. (2024, 15 Januari). *Siaran Pers Nomor: 30.Pers/04/SJI/2024: DMO Terpenuhi, Produksi Batubara Lampau Target 2023*.
- Lachman, J., Balas, M., Lisy, M., Lisa, H., Milcak, P., & Elbl, P. (2021). An overview of *slagging* and *fouling* indicators and their applicability to biomass fuels. *Fuel Processing Technology*, 217. <https://doi.org/10.1016/j.fuproc.2021.106804>
- Li, H., et al. (2022). Effect of coal blending on ash fusibility and slurrability of Xinjiang low-rank coal. *Processes*, 10(9), 1693.
- Li, J. (2016). *Effect of coal blending on ash fouling and slagging in pulverized coal-fired supercritical (SC) and ultra-supercritical (USC) power plants* (Master's thesis). The University of Western Australia.
- Luo, Z., & Agraniotis, M. (2017). *Low-rank coal for power generation, fuel and chemical production*. Cambridge: Woodhead Publishing.
- Miles, T. R., et al. (1996). Boiler deposits from firing biomass fuels. *Biomass and Bioenergy*, 10(2), 125–138. [https://doi.org/10.1016/0961-9534\(95\)00067-4](https://doi.org/10.1016/0961-9534(95)00067-4)
- Mitsubishi Heavy Industries (MHI). (2022). *Operation Manual Training for Paiton 3 Expansion Project*. POMI Training Manual.
- Plaza, P. P. (2013). *Fouling: The development of a slagging and scale predictive methodology for large pulverised boilers fired blends of coal/biomass* (Doctoral dissertation). Cardiff University.
- Prakoso, S. J. (2024). Dampak penurunan nilai kalori batubara pada efisiensi boiler dan biaya bahan bakar pada PLTU Paiton Unit 3 Probolinggo Jawa Timur.
- Prismantoko, D., et al. (2024). Ash deposition behavior during co-combustion of solid recovered fuel with different coals. *Thermal Science and Engineering Progress*, 48, Article 102404.
- Raask, E. (1985). *Mineral impurities in coal combustion: Behaviour, problems, remedial measures*. Washington DC: Hemisphere Publishing Corporation.
- Rasgianti, R., Cahyo, N., Supriyanto, E., Sitanggang, R. B., & Triani, M. (2021). The performance of Pacitan power plant (pulverized boiler) toward the blending coal: An experimental. *IOP Conference Series: Earth and Environmental Science*, 882, 01203.
- Ren, Y., Wu, Q., Wen, M., Li, G., Xu, L., Ding, X., et al. (2020). Sulfur trioxide emissions from coal-fired power plants in China and implications on future control. *Fuel*, 261, 116438.
- Saputra, D., Triantoro, A., dan Riswan. (2013). Simulasi blending batubara di bawah standar kontrak dalam blending dua jenis grade beda kualitas pada PT Amanah Anugerah Adi Mulia Site Kintap.
- Singh, S. (2012). Pre-determination of the *fouling* and cleanliness factor of the heat exchanger. *International Journal of Engineering Research and Application*, 2, 1177–1179.
- Sloss, L. (2014). *Blending of coals to meet power station requirements*. London.

Stultz, S. C., & Kitto, J. B. (Eds.). (2005). *Steam: Its generation and use* (40th ed.). Ohio: The Babcock & Wilcox Company.

Sudewa, I. P. (2022). Analisis variasi penggunaan batubara terhadap efisiensi boiler pada PLTU Paiton Unit 8. Departemen Teknik Mesin ITS Surabaya.

Suhaily, H. (2024). Analisis pengaruh sliding pressure operation pada subcritical boiler terhadap performa PLTU Paiton Unit 8.

Suhaily, H. (2015). *Power Plant Knowledge-Boiler*. PT. Paiton Operation & Maintenance Indonesia, Paiton, Probolinggo.

Xiao et al. (2014) Thermodynamic Modeling of Ash *Slagging* Characteristics in Coal Combustion, *Fuel*, 123, 194–203

Y., Zhihao, et al. (2021). Understanding effect of phosphorus-based additive on ash deposition characteristics during high-sodium and high-calcium Zhundong coal combustion in drop-tube furnace. *Fuel*, 287, 119462.

