

DAFTAR PUSTAKA

- [1] Pusat Data dan Sistem Informasi Pertanian, “Outlook Cabai Tahun 2024,” Sekretariat Jenderal Kementerian Pertanian, Jakarta, 2025, ISSN 1907-1507. Tersedia: https://satudata.pertanian.go.id/assets/docs/publikasi/OUTLOOK_CABAI_2024_.pdf
- [2] M. U. Masood and M. Haghshenas-Jaryani, “A Study on the Feasibility of Robotic Harvesting for Chile Pepper,” *Robotics*, vol. 10, no. 3, art. 94, 2021, doi: 10.3390/robotics10030094. Tersedia: <https://www.mdpi.com/2218-6581/10/3/94>
- [3] W. Han, J. Luo, J. Wang, Q. Gu, L. Lin, Y. Gao, H. Chen, K. Luo, Z. Zeng, and J. He, “Design of a Chili Pepper Harvesting Device for Hilly Chili Fields,” *Agronomy*, vol. 15, no. 5, art. 1118, 2025, doi: 10.3390/agronomy15051118. Tersedia: <https://www.mdpi.com/2073-4395/15/5/1118>
- [4] A. Paul and R. Machavaram, “Design, Kinematic Modeling, and Hybrid AI-Based Optimization of a Vision-Guided 6-DOF Robotic Arm for Capsicum Harvesting in Greenhouse Environments,” *Franklin Open*, vol. 12, art. 100388, 2025, doi: 10.1016/j.fraope.2025.100388. Tersedia: <https://www.sciencedirect.com/science/article/pii/S2773186325001768>
- [5] Y. Ge, Y. Xiong, G. L. Tenorio, and P. J. From, “Fruit Localization and Environment Perception for Strawberry Harvesting Robots,” *IEEE Access*, vol. 7, pp. 147642–147652, 2019, doi: 10.1109/ACCESS.2019.2946369. Tersedia: <https://ieeexplore.ieee.org/document/8863343>
- [6] Y. Yu, K. Zhang, H. Liu, L. Yang, and D. Zhang, “Real-Time Visual Localization of the Picking Points for a Ridge-Planting Strawberry Harvesting Robot,” *IEEE Access*, vol. 8, pp. 116556–116568, 2020, doi: 10.1109/ACCESS.2020.3003034. Tersedia: <https://ieeexplore.ieee.org/document/9119372>
- [7] G. Hu, C. Chen, J. Chen, L. Sun, A. Sugirbay, Y. Chen, H. Jin, S. Zhang, and L. Bu, “Simplified 4-DOF Manipulator for Rapid Robotic Apple Harvesting,” *Computers and Electronics in Agriculture*, vol. 199, art. 107177, 2022, doi: 10.1016/j.compag.2022.107177. Tersedia: <https://www.sciencedirect.com/science/article/pii/S016816992200494X>
- [8] E. J. Van Henten, D. A. Van’t Slot, C. W. J. Hol, and L. G. Van Willigenburg, “Optimal Manipulator Design for a Cucumber Harvesting Robot,” *Computers and Electronics in Agriculture*, vol. 65, no. 2, pp. 247–257, 2009, doi: 10.1016/j.compag.2008.11.004. Tersedia: <https://www.sciencedirect.com/science/article/pii/S0168169908002238>
- [9] K. Zhang, K. Lammers, P. Chu, Z. Li, and R. Lu, “System Design and Control of an Apple Harvesting Robot,” *Mechatronics*, vol. 79, art. 102644, 2021, doi: 10.1016/j.mechatronics.2021.102644. Tersedia: <https://www.sciencedirect.com/science/article/pii/S0957415821001173>; versi terbuka: <https://arxiv.org/abs/2010.11296>

- [10] A. Tai, M. Chun, Y. Gan, M. Selamet, and H. Lipson, "PARA: A One-Meter Reach, Two-Kg Payload, Three-DoF Open Source Robotic Arm with Customizable End Effector," *HardwareX*, vol. 10, art. e00209, 2021, doi: 10.1016/j.ohx.2021.e00209. Tersedia: <https://www.sciencedirect.com/science/article/pii/S2468067221000389>
- [11] A. J. Elias and J. T. Wen, "IK-Geo: Unified Robot Inverse Kinematics Using Subproblem Decomposition," *Mechanism and Machine Theory*, vol. 209, art. 105971, 2025, doi: 10.1016/j.mechmachtheory.2025.105971. Tersedia: <https://www.sciencedirect.com/science/article/pii/S0094114X25000606>
- [12] STMicroelectronics, "STM32F411xC/xE Datasheet: Arm Cortex-M4 32-bit MCU + FPU, 100 MHz, up to 512 KB Flash," STMicroelectronics. Tersedia: <https://www.st.com/resource/en/datasheet/stm32f411ce.pdf>
- [13] STMicroelectronics, "RM0383: STM32F411xC/E Advanced Arm-Based 32-bit MCUs Reference Manual," STMicroelectronics. Tersedia: https://www.st.com/resource/en/reference_manual/rm0383-stm32f411xce-advanced-armbased-32bit-mcus-stmicroelectronics.pdf
- [14] NVIDIA, "Jetson Orin Nano Super Developer Kit," NVIDIA, spesifikasi resmi. Tersedia: <https://www.nvidia.com/en-us/autonomous-machines/embedded-systems/jetson-orin/nano-super-developer-kit/>; dokumentasi pengembang: <https://docs.nvidia.com/jetson/orin-nano-devkit/user-guide/index.html>
- [15] V. D. Cong, "Design and Development of a Cost-Efficiency Robot Arm with a PLC-Based Robot Controller," *FME Transactions*, vol. 52, no. 2, pp. 226–236, 2024, doi: 10.5937/fme2402226C. Tersedia: https://www.mas.bg.ac.rs/_media/istrazivanje/fme/vol52/2/6_v._d._cong.pdf
- [16] H. He and Y. Dan, "The Research and Design of Smart Mobile Robotic Arm Based on Gesture Controlled," in *2020 International Conference on Advanced Mechatronic Systems (ICAMechS)*, Hanoi, Vietnam, 2020, pp. 308–312, doi: 10.1109/ICAMechS49982.2020.9310156. Tersedia: <https://ieeexplore.ieee.org/document/9310156>
- [17] Shenzhen XPTEK Technology Co., Ltd., "XPT2046 4-Wire Resistive Touch Screen Controller," XPTEK, laman produk resmi. Tersedia: <https://www.xptek.com.cn/cn/productview.asp?id=326>; salinan datasheet pabrikan: https://datasheet.lcsc.com/lcsc/1810181723_XPT-Shenzhen-XPTEK-Tech-XPT2046_C19076.pdf
- [18] F. Lozer, L. Scalera, P. Boscariol, and A. Gasparetto, "Planning Optimal Minimum-Jerk Trajectories for Redundant Robots," *Robotics and Autonomous Systems*, vol. 192, art. 105049, 2025, doi: 10.1016/j.robot.2025.105049. Tersedia: <https://www.sciencedirect.com/science/article/pii/S0921889025001356>
- [19] STMicroelectronics, "STM32CubeMX: STM32 Configuration and Initialization C Code Generation Tool," STMicroelectronics. Tersedia: <https://www.st.com/en/development-tools/stm32cubemx>
- [20] STMicroelectronics, "STM32CubeIDE: Integrated Development Environment for STM32," STMicroelectronics. Tersedia: <https://www.st.com/en/development-tools/stm32cubeide.html>

- [21] STMicroelectronics, “ST-LINK/V2 In-Circuit Debugger/Programmer for STM8 and STM32,” STMicroelectronics. Tersedia: <https://www.st.com/en/development-tools/st-link-v2.html>
- [22] Toshiba Electronic Devices & Storage Corporation, “TB6600HG Stepping Motor Driver IC,” Toshiba, datasheet/product information. Tersedia: <https://toshiba.semicon-storage.com/ap-en/semiconductor/product/motor-driver-ics/stepping-motor-driver-ics/detail.TB6600HG.html>
- [23] Dongguan City Dsservo Technology Co., Ltd., “DS3225 Product Datasheet: 6V 25kg RC Digital Servo,” DSSERVO, 2018. Tersedia: https://www.dsservo.com/d_file/DS3225%20datasheet.pdf
- [24] Allegro MicroSystems, “A3141, A3142, A3143, and A3144 Sensitive Hall Effect Switches for High-Temperature Operation,” datasheet. Tersedia: <https://www.allegromicro.com/~media/Files/Datasheets/A3141-2-3-4-Datasheet.ashx?la=en>
- [25] Gates Corporation, “Industrial Timing Belt Design Manual” dan “Industrial Power Transmission Preventive Maintenance Manual,” bagian PowerGrip HTD. Tersedia: <https://www.gates.com/content/dam/documents-library/catalogs/industrial-timing-belt-design-manual-kr.pdf> dan <https://www.gates.com/content/dam/gates/home/knowledge-center/resource-library/operating-manuals/preventive-maintenance-manual-en.pdf>
- [26] XLSEMI, “XL4016: 12A 180kHz 40V Buck DC to DC Converter Datasheet,” Rev. 1.6. Tersedia: <https://www.xlsemi.com/datasheet/XL4016-EN.pdf>
- [27] ILI Technology Corp., “ILI9341 a-Si TFT LCD Single Chip Driver, 240RGB×320 Resolution and 262K Color, Datasheet,” Version 1.13. Salinan datasheet pabrikan tersedia: <https://cdn-shop.adafruit.com/datasheets/ILI9341.pdf>
- [28] Suzhou Penny Machinery Equipment Co., Ltd. (G-Penny), situs resmi produsen: <https://gpennymachine.com/> ; spesifikasi varian NEMA 23 yang sesuai dengan komponen penelitian diverifikasi melalui identitas/nameplate komponen dan listing produk pemasok: https://www.alibaba.com/product-detail/G-Penny-NEMA-23-CNC-Stepper_1601252370390.html
- [29] National Institute of Standards and Technology (NIST), “SP 330 - The International System of Units (SI), Section 2,” NIST. Tersedia: <https://www.nist.gov/pml/special-publication-330/sp-330-section-2>
- [30] K. Zhang, K. Lammers, P. Chu, Z. Li, and R. Lu, “An Automated Apple Harvesting Robot—From System Design to Field Evaluation,” *Journal of Field Robotics*, vol. 41, no. 7, pp. 2384–2400, 2024, doi: 10.1002/rob.22268. Tersedia: <https://doi.org/10.1002/rob.22268>
- [31] B. Siciliano, L. Sciavicco, L. Villani, and G. Oriolo, *Robotics: Modelling, Planning and Control*. London: Springer, 2009, doi: 10.1007/978-1-84628-642-1. Tersedia: <https://doi.org/10.1007/978-1-84628-642-1>
- [32] WeAct Studio, “WeActStudio.MiniSTM32F4x1: MiniF4-STM32F401CEU6/STM32F411CEU6 Product Literature,” GitHub. Dokumentasi papan dan diagram distribusi pin tersedia: <https://github.com/WeActStudio/WeActStudio.MiniSTM32F4x1> (diakses 21 September 2026).

- [33] WeAct Studio MiniDebugger, foto produk dan identifikasi perangkat STLink V2.1, Elektroweb. Tersedia: <https://elektroweb.pl/pl/programatory/1791-stlink-v21-weact-mini-debugger-stm32-swd-swo-usb-c-st-link-przewody.html> ; dokumentasi proyek: <https://github.com/WeActStudio/WeActStudio.MiniDebugger> (diakses 21 September 2026).
- [34] Sorotec, “TB6600 — Stepper Motor Driver,” datasheet modul TB6600, termasuk foto modul dan konfigurasi terminal/DIP switch. Tersedia: https://components101.com/sites/default/files/component_datasheet/TB6600-Datasheet.pdf (diakses 21 September 2026).
- [35] iArduino, “Servo horn 25T,” foto DS3225MG dengan horn aluminium 25T. Tersedia: <https://iarduino.ru/shop/Mekanika/servo-horn-25t.html> (diakses 21 September 2026). Spesifikasi servo tetap mengacu pada datasheet resmi DSSERVO [23].
- [36] Alibaba.com, “Electronics New and Original A3144/OH3144/44E/AH3144E TO-92 Hall Effect Sensor,” foto sensor bertanda 3144 515. Tersedia: <https://www.alibaba.com/showroom/44e-hall-effect-sensor.html> (diakses 21 September 2026). Spesifikasi sensor tetap mengacu pada datasheet Allegro [24].
- [37] eBay, “300W XL4016 DC-DC Max 9A Buck Converter 5-40V to 1.2-35V Adjustable,” foto modul XL4016 dengan empat kapasitor, induktor toroidal, dan dua heatsink. Tersedia: <https://www.ebay.com/itm/176457687337> (diakses 21 September 2026). Spesifikasi IC tetap mengacu pada datasheet XLSEMI [26].
- [38] Digilog, “MSP2807 2.8 Inch 320×240 SPI Serial TFT LCD Module Display Screen with Touch Panel Driver IC ILI9341,” foto modul TFT merah dengan layar 2,8 inch dan pengendali sentuh. Tersedia: <https://digilog.pk/products/msp2807-2-8-inch-320-240-spi-serial-tft-lcd-module-display-screen-with-touch-panel-driver-ic-ili9341-for-mcu> (diakses 21 September 2026). Dokumentasi teknis modul juga tersedia pada LCDwiki: https://www.lcdwiki.com/2.8inch_SPI_Module_ILI9341_SKU%3AMSP2807.
- [39] G-PENNY MACHINE, “NEMA 23 CNC Stepper Motor 57×82 mm, 3 A, 2.2 N·m, model 57HS8230A4D8,” product listing mirror. Tersedia: <https://irl.grandado.com/products/nema-23-cnc-stepper-motor-57x82mm-3a-2-2n-m-d-8mm-6-35mm-315oz-in-nema23-cnc-router-engraving-milling-machine-3d-printer> (diakses 21 September 2026).